

Solutions**Problem 1:**

a) Spherical Coordinates:

Inserting the gradient expression into the Boltzmann equation in Cartesian coordinates and writing the scalar products explicitly gives:

$$\frac{\partial f}{\partial t} + v_r \frac{\partial f}{\partial r} + \frac{v_\theta}{r} \frac{\partial f}{\partial \theta} + \frac{v_\phi}{r \sin \phi} \frac{\partial f}{\partial \phi} + \dot{v}_r \frac{\partial f}{\partial v_r} + \dot{v}_\theta \frac{\partial f}{\partial v_\theta} + \dot{v}_\phi \frac{\partial f}{\partial v_\phi} = 0 \quad (1)$$

We have

$$v_r = \dot{r}, \quad v_\theta = r\dot{\theta}, \quad v_\phi = r \sin \theta \dot{\phi}$$

and the Lagrangian

$$L = \frac{1}{2} \left(\dot{r}^2 + r^2 \dot{\theta}^2 + r^2 \sin^2 \theta \dot{\phi}^2 \right) - \Phi(r)$$

To obtain the Equations of Motion, we use

$$\frac{d}{dt} \frac{\partial L}{\partial \dot{q}_i} - \frac{\partial L}{\partial q_i} = 0$$

For $q_i = r$:

$$\begin{aligned} \frac{d}{dt} \dot{r} - r\dot{\theta}^2 - r \sin^2 \theta \dot{\phi}^2 + \frac{\partial \Phi}{\partial r} &= 0 \\ \dot{v}_r &= \frac{v_\theta^2 + v_\phi^2}{r} - \frac{\partial \Phi}{\partial r} \end{aligned}$$

For $q_i = \theta$:

$$\begin{aligned} \frac{d}{dt} \left(r^2 \dot{\theta} \right) - r^2 \sin \theta \cos \theta \dot{\phi}^2 &= 0 = \frac{d}{dt} \left(r \cdot (r\dot{\theta}) \right) - (r \sin \theta \dot{\phi})^2 \frac{\cos \theta}{\sin \theta} \\ \frac{d}{dt} \left(r\dot{\theta} \right) &= \frac{1}{r} \left(\frac{(r \sin \theta \dot{\phi})^2}{\tan \theta} - \dot{r}(r\dot{\theta}) \right) \\ \dot{v}_\theta &= \frac{1}{r} \left(\frac{v_\phi^2}{\tan \theta} - v_r v_\theta \right) \end{aligned}$$

For $q_i = \phi$:

$$\begin{aligned}\frac{d}{dt} \left(r^2 \sin^2 \theta \dot{\phi} \right) &= 0 = \frac{d}{dt} \left(r \sin \theta \cdot (r \sin \theta \dot{\phi}) \right) \\ \frac{d}{dt} \left(r \sin \theta \dot{\phi} \right) &= -(r \sin \theta \dot{\phi}) \left(\frac{\dot{r}}{r} + \frac{r\dot{\theta}}{r \tan \theta} \right) \\ \dot{v}_\phi &= -\frac{v_\phi}{r} \left(v_r + \frac{v_\theta}{\tan \theta} \right)\end{aligned}$$

Inserting \dot{v}_r , \dot{v}_θ , \dot{v}_ϕ into expression (1) gives the required result.

b) Cylindrical Coordinates:

Inserting the gradient expression into the Boltzmann equation in Cartesian coordinates and writing the scalar products explicitly gives:

$$\frac{\partial f}{\partial t} + v_r \frac{\partial f}{\partial r} + \frac{v_\phi}{r} \frac{\partial f}{\partial \phi} + v_z \frac{\partial f}{\partial z} + \dot{v}_r \frac{\partial f}{\partial v_r} + \dot{v}_\phi \frac{\partial f}{\partial v_\phi} + \dot{v}_z \frac{\partial f}{\partial v_z} = 0 \quad (2)$$

We have

$$v_r = \dot{r}, \quad v_\phi = r\dot{\phi}, \quad v_z = \dot{z}$$

and the Lagrangian

$$L = \frac{1}{2} \left(\dot{r}^2 + r^2 \dot{\phi}^2 + \dot{z}^2 \right) - \Phi(r, z)$$

To obtain the Equations of Motion, we use

$$\frac{d}{dt} \frac{\partial L}{\partial \dot{q}_i} - \frac{\partial L}{\partial q_i} = 0$$

For $q_i = r$:

$$\begin{aligned}\frac{d}{dt} \dot{r} - r\dot{\phi}^2 + \frac{\partial \Phi}{\partial r} &= 0 \\ \dot{v}_r &= \frac{v_\phi^2}{r} - \frac{\partial \Phi}{\partial r}\end{aligned}$$

For $q_i = \phi$:

$$\begin{aligned}\frac{d}{dt} \left(r^2 \dot{\phi} \right) - 0 &= 0 = \frac{d}{dt} \left(r \cdot (r\dot{\phi}) \right) \\ \frac{d}{dt} \left(r\dot{\phi} \right) &= -\frac{1}{r} \dot{r} \cdot r\dot{\phi} \\ \dot{v}_\phi &= -\frac{v_r v_\phi}{r}\end{aligned}$$

For $q_i = z$:

$$\begin{aligned}\frac{d}{dt}\dot{z} + \frac{\partial\Phi}{\partial z} &= 0 \\ \dot{v}_z &= -\frac{\partial\Phi}{\partial z}\end{aligned}$$

Inserting \dot{v}_r , \dot{v}_ϕ , \dot{v}_z into expression (2) gives the required result.

Problem 2:

In Cartesian coordinates, the collisionless Boltzmann equation writes:

$$\frac{\partial f}{\partial t} + \mathbf{v} \cdot \frac{\partial f}{\partial \mathbf{x}} + \mathbf{a} \cdot \frac{\partial f}{\partial \mathbf{v}} = 0. \quad (3)$$

The only term that will be influenced by the rotation is the acceleration \mathbf{a} . In a rotating frame, the Lagrangian is:

$$L = \frac{1}{2}(\mathbf{v} + \boldsymbol{\Omega} \times \mathbf{x})^2 - \Phi(\mathbf{x}) \quad (4)$$

Defining the effective potential as:

$$\Phi_{\text{eff}}(\mathbf{x}) = \Phi(\mathbf{x}) - \frac{1}{2}(\boldsymbol{\Omega} \times \mathbf{x})^2, \quad (5)$$

the Lagrangian writes:

$$L = \frac{1}{2}\mathbf{v}^2 + \mathbf{v}(\boldsymbol{\Omega} \times \mathbf{x}) - \Phi_{\text{eff}}(\mathbf{x}). \quad (6)$$

Using the Euler-Lagrange equation we get:

$$\mathbf{a} = -\nabla\Phi_{\text{eff}}(\mathbf{x}) - 2(\boldsymbol{\Omega} \times \mathbf{v}) \quad (7)$$

We conclude that the collisionless Boltzmann equation in the rotating frame writes:

$$\frac{\partial f}{\partial t} + \mathbf{v} \cdot \frac{\partial f}{\partial \mathbf{x}} - [\nabla\Phi_{\text{eff}}(\mathbf{x}) + 2(\boldsymbol{\Omega} \times \mathbf{v})] \cdot \frac{\partial f}{\partial \mathbf{v}} = 0. \quad (8)$$